

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Alkalisch schuim super
Product code : UAC 11300

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Consumer use
Use of the substance/mixture : Cleaning/washing agents and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

HeiQ Chrisal
Priester Daensstraat 9
BE- 3920 3920 - Lommel
België
T 0032 11 54 80 00
info.be@heiq.com - www.chrisal.com

1.4. Emergency telephone number

Emergency number : +32 70 245 245

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Corrosive to metals, Category 1 H290
Skin corrosion/irritation, Category 1 H314
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May be corrosive to metals. Causes severe skin burns and eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

Signal word (CLP) : Danger
Hazard statements (CLP) : H290 - May be corrosive to metals.
H314 - Causes severe skin burns and eye damage.
Precautionary statements (CLP) : P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P280 - Wear protective clothing/eye protection/face protection, protective gloves.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P363 - Wash contaminated clothing before reuse.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rinse skin with water or shower.
P260 - Do not breathe dusts or mists.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
potassium hydroxide; caustic potash	CAS-No.: 1310-58-3 EC-No.: 215-181-3 EC Index-No.: 019-002-00-8 REACH-no: 01-2119487136-33	$\geq 5 - < 10$	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Met. Corr. 1, H290
sodium hydroxide; caustic soda	CAS-No.: 1310-73-2 EC-No.: 215-185-5 EC Index-No.: 011-002-00-6 REACH-no: 01-2119457892-27	$\geq 5 - < 10$	Skin Corr. 1A, H314 Eye Dam. 1, H318 Met. Corr. 1, H290
Alkyl, C8-10, polyglucoside	CAS-No.: 68515-73-1 EC-No.: 500-220-1 REACH-no: 01-2119488530-36	$\geq 1 - < 5$	Eye Dam. 1, H318
2-(2-butoxyethoxy)ethanol substance with a Community workplace exposure limit	CAS-No.: 112-34-5 EC-No.: 203-961-6 EC Index-No.: 603-096-00-8	$\geq 0,1 - < 1$	Eye Irrit. 2, H319
Amines, coco alkyldimethyl, N-oxides	CAS-No.: 61788-90-7 EC-No.: 263-016-9	$\geq 0,1 - < 1$	Eye Dam. 1, H318 Skin Irrit. 2, H315 Aquatic Acute 1, H400

Specific concentration limits:

Name	Product identifier	Specific concentration limits
potassium hydroxide; caustic potash	CAS-No.: 1310-58-3 EC-No.: 215-181-3 EC Index-No.: 019-002-00-8 REACH-no: 01-2119487136-33	(0,5 \leq C < 2) Skin Irrit. 2, H315 (0,5 \leq C < 2) Eye Irrit. 2, H319 (2 \leq C < 5) Skin Corr. 1B, H314 (5 \leq C < 100) Skin Corr. 1A, H314
sodium hydroxide; caustic soda	CAS-No.: 1310-73-2 EC-No.: 215-185-5 EC Index-No.: 011-002-00-6 REACH-no: 01-2119457892-27	(0,5 \leq C < 2) Skin Irrit. 2, H315 (0,5 \leq C < 2) Eye Irrit. 2, H319 (2 \leq C < 5) Skin Corr. 1B, H314 (5 \leq C < 100) Skin Corr. 1A, H314

Full text of H- and EUH-statements: see section 16

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Not flammable.
-------------	------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

To our knowledge, the product does not present any particular risk, under normal conditions of use.

6.3. Methods and material for containment and cleaning up

Other information	: Dispose of materials or solid residues at an authorized site.
-------------------	---

6.4. Reference to other sections

For further information refer to section 13.

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in original container. Store in a well-ventilated place. Keep cool.
- Incompatible materials : Metals.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

2-(2-butoxyethoxy)ethanol (112-34-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-(2-Butoxyethoxy)ethanol
IOEL TWA	67,5 mg/m ³
IOEL TWA [ppm]	10 ppm
IOEL STEL	101,2 mg/m ³
IOEL STEL [ppm]	15 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Albania - Occupational Exposure Limits	
Local name	(Butoksi-2-etoksi)-2-etanol
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES "PËR MBROJTJEN E SIGURISË DHE SHËNDËTIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË"
Austria - Occupational Exposure Limits	
Local name	Butyldiglykol (Butoxydiethylenglykol; 2-(2-Butoxyethoxy)-ethanol; Diethylenglykolmonobutylether)
MAK (OEL TWA)	67,5 mg/m ³
MAK (OEL TWA) [ppm]	10 ppm
MAK (OEL STEL)	101,2 mg/m ³ (4x 15(Miw) min)
MAK (OEL STEL) [ppm]	15 ppm (4x 15(Miw) min)
Regulatory reference	BGBl. II Nr. 156/2021

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-(2-butoxyethoxy)ethanol (112-34-5)	
Belgium - Occupational Exposure Limits	
Local name	2-(2-Butoxyéthoxy)éthanol # 2-(2-Butoxyethoxy)ethanol
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	2-(2-Бутокси-етокси) етанол
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	2-(2-Butoksietoksi)etanol; dietilen-glikol monobutil-eter
GVI (OEL TWA) [1]	67,5 mg/m ³
GVI (OEL TWA) [2]	10 ppm
KGVI (OEL STEL)	101,2 mg/m ³
KGVI (OEL STEL) [ppm]	15 ppm
Remark	Direktiva: 2006/15/EZ
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граниčnim vrijednostima izloženosti i biološkim граниčnim vrijednostima (NN 1/2021)
Cyprus - Occupational Exposure Limits	
Local name	2-(2-Βουτοξυαιθοξυ)αιθανόλη
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
Czech Republic - Occupational Exposure Limits	
Local name	2-(2-Buthoxyethoxy)ethanol (Butyldiglykol)
PEL (OEL TWA)	70 mg/m ³
PEL (OEL TWA) [ppm]	10 ppm
NPK-P (OEL C)	100 mg/m ³
NPK-P (OEL C) [ppm]	15 ppm

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-(2-butoxyethoxy)ethanol (112-34-5)	
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Butyldiglycol
OEL TWA [1]	68 mg/m ³
OEL TWA [2]	10 ppm
OEL STEL	101 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi)
Regulatory reference	BEK nr 1054 af 28/06/2022
Finland - Occupational Exposure Limits	
Local name	2-(2-Butoksietoksi)etanoli
HTP (OEL TWA) [1]	68 mg/m ³
HTP (OEL TWA) [2]	10 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)éthanol
VME (OEL TWA)	67,5 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	101,2 mg/m ³
VLE (OEL C/STEL) [ppm]	15 ppm
Remark	Valeurs réglementaires indicatives
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-(2-Butoxyethoxy)ethanol
AGW (OEL TWA) [1]	67 mg/m ³
AGW (OEL TWA) [2]	10 ppm
Peak exposure limitation factor	1,5(l)
Remark	EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; 11 - Summe aus Dampf und Aerosolen
Regulatory reference	TRGS900
Gibraltar - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-(2-butoxyethoxy)ethanol (112-34-5)	
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	2-(2-βουτοξυαιθοξυ) αιθανόλη
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Π.Δ. 162/2007 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	2-(2-BUTOXIETOXI)ETANOL
AK (OEL TWA)	67,5 mg/m ³
CK (OEL STEL)	101,2 mg/m ³
Remark	EU2 (2006/15/EK irányelvben közölt érték); T (Azok az anyagok, amelyek egészségkárosító hatása TARTÓS expozíciót követően jelentkezik)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
OEL TWA [1]	67,5 mg/m ³
OEL TWA [2]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Italy - Occupational Exposure Limits	
Local name	2-(2-Butossietossi)etanolo
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	2-(2-Butoksietoksi) etanols (butilidglikols)
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumiem Nr. 92)

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-(2-butoxyethoxy)ethanol (112-34-5)	
Lithuania - Occupational Exposure Limits	
Local name	2-(2-butoksietoksi)etanolis (dietilenglikolio monobutyleteris, oksidietanolio monobutyleteris)
IPRV (OEL TWA)	67,5 mg/m ³
IPRV (OEL TWA) [ppm]	10 ppm
TPRV (OEL STEL)	101,2 mg/m ³
TPRV (OEL STEL) [ppm]	15 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	2-(2-butoxyéthoxy)éthanol
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
Netherlands - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
TGG-8u (OEL TWA)	50 mg/m ³
TGG-8u (OEL TWA) [ppm]	7,4 ppm
TGG-15min (OEL STEL)	100 mg/m ³
TGG-15min (OEL STEL) [ppm]	14,8 ppm
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2023
Poland - Occupational Exposure Limits	
Local name	2-(2-Butoksyetoksy)etanol
NDS (OEL TWA)	67 mg/m ³
NDSCh (OEL STEL)	100 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	2-(2-Butoxietoxi) etanol (éter dietilenoglicol monobutílico)

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-(2-butoxyethoxy)ethanol (112-34-5)	
OEL TWA [ppm]	10 ppm FIV (Fração inalável e vapor)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	2-(2-Butoxiatoxi)-etanol/Dowanol DB
OEL TWA	67,5 mg/m ³ 10 mg/m ³
OEL STEL	101,2 mg/m ³ 15 mg/m ³
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Serbia - Occupational Exposure Limits	
Local name	2-(2-буксоксиетокси)етанол; диетилен-гликол монобутил-етар
OEL TWA	68 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	ЕУ** – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2006/15/ЕЗ (друга листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovakia - Occupational Exposure Limits	
Local name	Butyldiglykol 2-(2-butoxyetoxy)etanol
NPHV (OEL TWA) [1]	67,5 mg/m ³
NPHV (OEL TWA) [2]	10 ppm
NPHV (OEL STEL)	101,2 mg/m ³
NPHV (OEL STEL) [ppm]	15 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	2-(2-butoksietoksi)etanol (butildietilenglikol)
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	2-(2-Butoxiatoxi) etanol (Dietilenglicol monobutiléter)
VLA-ED (OEL TWA) [1]	67,5 mg/m ³
VLA-ED (OEL TWA) [2]	10 ppm
VLA-EC (OEL STEL)	101,2 mg/m ³
VLA-EC (OEL STEL) [ppm]	15 ppm

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-(2-butoxyethoxy)ethanol (112-34-5)	
Remark	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
Local name	Dietylenglykolmonobutyleter
NGV (OEL TWA)	68 mg/m ³
NGV (OEL TWA) [ppm]	10 ppm
KTV (OEL STEL)	101 mg/m ³
KTV (OEL STEL) [ppm]	15 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
WEL TWA (OEL TWA) [1]	67,5 mg/m ³
WEL TWA (OEL TWA) [2]	10 ppm
WEL STEL (OEL STEL)	101,2 mg/m ³
WEL STEL (OEL STEL) [ppm]	15 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	2-(2-bútoxýetoxý)etanól (bútýldíglykól)
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101,2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	2-(2(butoksyetoksy)etanol
Grenseverdi (OEL TWA) [1]	68 mg/m ³
Grenseverdi (OEL TWA) [2]	10 ppm
Remark	E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	2-(2-бутоксietокси) етанол (бутилдиетиленгликол)
OEL TWA	67,5 mg/m ³
OEL TWA [ppm]	10 ppm
KTV	1,5

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-(2-butoxyethoxy)ethanol (112-34-5)	
Short time value [mg/m ³]	101,25 mg/m ³
Short time value [ppm]	15 ppm
Remark	(*) дополнување на граничната вредност заради донесената Директива на Комисијата 2006/15ES од 7 февруари 2006 за создавање на втора листа на индикативни гранични вредности за професионална изложеност според директивата 98/24/EC и за измените на директивата 91/322/EEC и директивата 2000/39/ EC (Сл. весник бр. 38 од ден 9.2.2006, стр. 36); (KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Butyldiglycol / Butyldiglykol [Diethylenglykolmonobutylether]
MAK (OEL TWA) [1]	67 mg/m ³
MAK (OEL TWA) [2]	10 ppm
KZGW (OEL STEL)	101 mg/m ³
KZGW (OEL STEL) [ppm]	15 ppm
Critical toxicity	Rein, Sang, Foie / Niere, Blut, Leber
Notation	SS _c / SS _c
Regulatory reference	www.suva.ch, 01.01.2023
USA - ACGIH - Occupational Exposure Limits	
Local name	Diethylene glycol monobutyl ether
ACGIH OEL TWA [ppm]	10 ppm (IFV - Inhalable fraction and vapor)
Remark (ACGIH)	TLV® Basis: Hematologic, liver & kidney eff
Regulatory reference	ACGIH 2023
sodium hydroxide; caustic soda (1310-73-2)	
Austria - Occupational Exposure Limits	
Local name	Natriumhydroxid (Ätznatron)
MAK (OEL TWA)	2 mg/m ³ (E)
MAK (OEL STEL)	4 mg/m ³ (E, 8x 5(Mow) min)
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Sodium (hydroxyde de) # Natriumhydroxide
OEL TWA	2 mg/m ³

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

sodium hydroxide; caustic soda (1310-73-2)	
Remark	M: la mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage. # M: de vermelding "M" duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkproces moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Натриева основа
OEL TWA	2 mg/m ³ (алкални аерозоли)
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Natrijev hidroksid; kaustična soda
KGVI (OEL STEL)	2 mg/m ³
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граниčnim vrijednostima izloženosti i biološkim граниčnim vrijednostima (NN 1/2021)
Czech Republic - Occupational Exposure Limits	
Local name	Hydroxid sodný
PEL (OEL TWA)	1 mg/m ³
NPK-P (OEL C)	2 mg/m ³
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Natriumhydroxid
OEL C	2 mg/m ³
Regulatory reference	BEK nr 1054 af 28/06/2022
Estonia - Occupational Exposure Limits	
Local name	Naatriumhüdroksiid
OEL TWA	1 mg/m ³
OEL STEL	2 mg/m ³ arvutatud 5-minutisele kokkupuuteajale
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
Finland - Occupational Exposure Limits	
Local name	Natriumhydroksidi
HTP (OEL C)	2 mg/m ³
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

sodium hydroxide; caustic soda (1310-73-2)	
France - Occupational Exposure Limits	
Local name	Sodium (hydroxyde de)
VME (OEL TWA)	2 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Greece - Occupational Exposure Limits	
Local name	Υδροξείδιο του νατρίου
OEL TWA	2 mg/m ³
OEL STEL	2 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	NÁTRIUM-HIDROXID
AK (OEL TWA)	1 mg/m ³
CK (OEL STEL)	2 mg/m ³
Remark	m (maró hatású anyag, amely felmarja a bőrt, nyálkahártyát, szemet vagy mindhármat); N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Sodium hydroxide
OEL STEL	2 mg/m ³
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
Local name	Nātrija hidroksīds (nātrija sārms, kaustiskā soda)
OEL TWA	0,5 mg/m ³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumiem Nr. 92)
Lithuania - Occupational Exposure Limits	
Local name	Natrio hidroksidas
NRV (OEL C)	2 mg/m ³
Remark	Ū (ūmus poveikis)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Poland - Occupational Exposure Limits	
Local name	Wodorotlenek sodu
NDS (OEL TWA)	0,5 mg/m ³
NDSCh (OEL STEL)	1 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	Hidróxido de sódio

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

sodium hydroxide; caustic soda (1310-73-2)	
OEL C [ppm]	2 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
Slovakia - Occupational Exposure Limits	
Local name	Hydroxid sodný
NPHV (OEL TWA) [1]	2 mg/m ³
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Spain - Occupational Exposure Limits	
Local name	Hidróxido de sodio
VLA-EC (OEL STEL)	2 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
Local name	Natriumhydroxid
NGV (OEL TWA)	1 mg/m ³ inhalerbar fraktion
KTV (OEL STEL)	2 mg/m ³ inhalerbar fraktion
Remark	3 (Med inhalerbar fraktion menas den mängd partiklar, av totalmängden partiklar i luften, som man inandas genom näsa och mun)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Sodium hydroxide
WEL STEL (OEL STEL)	2 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Natriumhýdroxíð (vítissóti)
OEL STEL	2 mg/m ³
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Natriumhydroksid
Takverdi (OEL C) [1]	2 mg/m ³
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	Натриум хидроксид
OEL TWA	2 mg/m ³ (l) инхалабилна фракција – дел на вкупно суспендирани материи, кои работникот ги вдишува
KTV	1
Short time value [mg/m ³]	2 mg/m ³

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

sodium hydroxide; caustic soda (1310-73-2)	
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покосо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (Y)
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Soude caustique / Natriumhydroxid [Aetznatron]
MAK (OEL TWA) [1]	2 mg/m ³ (i) / (e)
KZGW (OEL STEL)	2 mg/m ³ (i) / (e)
Critical toxicity	VRS, Peau, Yeux / OAW, Haut, Auge
Notation	SS _c / SS _c
Remark	NIOSH, OSHA
Regulatory reference	www.suva.ch, 01.01.2023
USA - ACGIH - Occupational Exposure Limits	
Local name	Sodium hydroxide
ACGIH OEL C	2 mg/m ³
Remark (ACGIH)	TLV® Basis: URT, eye, & skin irr
Regulatory reference	ACGIH 2023
potassium hydroxide; caustic potash (1310-58-3)	
Austria - Occupational Exposure Limits	
Local name	Kaliumhydroxid
MAK (OEL TWA)	2 mg/m ³ (E)
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Potassium (hydroxyde de) # Kaliumhydroxide
OEL STEL	2 mg/m ³
Remark	M: la mention “M” indique que lors d’une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d’intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l’exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d’échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d’échantillonnage. # M: de vermelding “M” duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkprocédé moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

potassium hydroxide; caustic potash (1310-58-3)	
Bulgaria - Occupational Exposure Limits	
Local name	Калиева основа
OEL TWA	2 mg/m ³
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Kalijev hidroksid; kaustična potaša
KGVI (OEL STEL)	2 mg/m ³
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Czech Republic - Occupational Exposure Limits	
Local name	Hydroxid draselný
PEL (OEL TWA)	1 mg/m ³
NPK-P (OEL C)	2 mg/m ³
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Kaliumhydroxid
OEL C	2 mg/m ³
Regulatory reference	BEK nr 1054 af 28/06/2022
Estonia - Occupational Exposure Limits	
Local name	Kaaliumhüdroksiid
OEL TWA	2 mg/m ³
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
Finland - Occupational Exposure Limits	
Local name	Kaliumhydroksidi
HTP (OEL C)	2 mg/m ³
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	Potassium (hydroxyde de)
VLE (OEL C/STEL)	2 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Greece - Occupational Exposure Limits	
Local name	Υδροξείδιο του καλίου
OEL TWA	2 mg/m ³
OEL STEL	2 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

potassium hydroxide; caustic potash (1310-58-3)	
Hungary - Occupational Exposure Limits	
Local name	KÁLIUM-HIDROXID
AK (OEL TWA)	2 mg/m ³
CK (OEL STEL)	2 mg/m ³
Remark	m (maró hatású anyag, amely felmarja a bőrt, nyálkahártyát, szemet vagy mindhármát); N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Potassium hydroxide
OEL STEL	2 mg/m ³
Regulatory reference	Chemical Agents Code of Practice 2021
Poland - Occupational Exposure Limits	
Local name	Wodorotlenek potasu
NDS (OEL TWA)	0,5 mg/m ³
NDSCh (OEL STEL)	1 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	Hidróxido de potássio
OEL C [ppm]	2 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
Spain - Occupational Exposure Limits	
Local name	Hidróxido de potasio
VLA-EC (OEL STEL)	2 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
Local name	Kaliumhydroxid
NGV (OEL TWA)	1 mg/m ³ inhalerbar fraktion
KTV (OEL STEL)	2 mg/m ³ inhalerbar fraktion
Remark	3 (Med inhalerbar fraktion menas den mängd partiklar, av totalmängden partiklar i luften, som man inandas genom näsa och mun)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Potassium hydroxide
WEL STEL (OEL STEL)	2 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Kaliumhýdroxíð
OEL STEL	2 mg/m ³

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

potassium hydroxide; caustic potash (1310-58-3)	
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Kaliumhydroksid
Takverdi (OEL C) [1]	2 mg/m ³
Regulatory reference	FOR-2021-06-28-2248
Switzerland - Occupational Exposure Limits	
Local name	Potasse caustique / Kaliumhydroxid
MAK (OEL TWA) [1]	2 mg/m ³ (i) / (e)
Critical toxicity	VRS, Peau, Yeux / OAW, Haut, Auge
Remark	NIOSH
Regulatory reference	www.suva.ch, 01.01.2023
USA - ACGIH - Occupational Exposure Limits	
Local name	Potassium hydroxide
ACGIH OEL C	2 mg/m ³
Remark (ACGIH)	TLV® Basis: URT, eye, & skin irr
Regulatory reference	ACGIH 2023

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	6 (> 480 minutes)	0.35		

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: ≥ 13
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Amines, coco alkyldimethyl, N-oxides (61788-90-7)

LD50 oral rat	1064 mg/kg
LD50 oral	> 2000 mg/kg bodyweight

2-(2-butoxyethoxy)ethanol (112-34-5)

LD50 oral	5660 mg/kg bodyweight
LD50 dermal	2764 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 196 mg/l

potassium hydroxide; caustic potash (1310-58-3)

LD50 oral	333 mg/kg bodyweight
-----------	----------------------

Alkyl, C8-10, polyglucoside (68515-73-1)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method)
LD50 oral	> 2000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal	> 2000 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns.
pH: ≥ 13
Serious eye damage/irritation : Assumed to cause serious eye damage
pH: ≥ 13
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aspiration hazard : Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Amines, coco alkyldimethyl, N-oxides (61788-90-7)

LC50 - Fish [1]	> 10 mg/l
EC50 - Crustacea [1]	3,1 mg/l
EC50 - Other aquatic organisms [2]	0,11 mg/l
EC50 72h - Algae [1]	0,19 mg/l

2-(2-butoxyethoxy)ethanol (112-34-5)

LC50 - Fish [1]	1300 mg/l
EC50 - Other aquatic organisms [1]	> 1000 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 100 mg/l

sodium hydroxide; caustic soda (1310-73-2)

LC50 - Fish [1]	> 35 mg/l
EC50 - Other aquatic organisms [1]	> 33 mg/l waterflea

potassium hydroxide; caustic potash (1310-58-3)

LC50 - Fish [1]	80 mg/l
-----------------	---------

Alkyl, C8-10, polyglucoside (68515-73-1)

LC50 - Fish [1]	100,81 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	170 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l waterflea
EC50 - Other aquatic organisms [2]	27,2 mg/l
EC50 72h - Algae [1]	27,22 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	37 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

12.2. Persistence and degradability

Amines, coco alkyldimethyl, N-oxides (61788-90-7)

Persistence and degradability : >90% % biodegradation (OECD 301D).

2-(2-butoxyethoxy)ethanol (112-34-5)

Persistence and degradability : Readily biodegradable.

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.3. Bioaccumulative potential

Amines, coco alkyldimethyl, N-oxides (61788-90-7)

Bioaccumulative potential	Bioaccumulation unlikely.
---------------------------	---------------------------

2-(2-butoxyethoxy)ethanol (112-34-5)

Partition coefficient n-octanol/water (Log Pow)	0,56
---	------

sodium hydroxide; caustic soda (1310-73-2)

Partition coefficient n-octanol/water (Log Pow)	-3,88
---	-------

potassium hydroxide; caustic potash (1310-58-3)

Partition coefficient n-octanol/water (Log Pow)	0,75
---	------

Alkyl, C8-10, polyglucoside (68515-73-1)

Partition coefficient n-octanol/water (Log Pow)	< 1,77
---	--------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information



In accordance with ADR / IATA

ADR	IATA
14.1. UN number or ID number	
UN 1719	UN 1719
14.2. UN proper shipping name	
CAUSTIC ALKALI LIQUID, N.O.S. (Mixture with sodium hydroxide, potassium hydroxide)	Caustic alkali liquid, n.o.s. (Mixture with sodium hydroxide, potassium hydroxide)
Transport document description	
UN 1719 CAUSTIC ALKALI LIQUID, N.O.S. (Mixture with sodium hydroxide, potassium hydroxide), 8, II, (E)	UN 1719 Caustic alkali liquid, n.o.s. (Mixture with sodium hydroxide, potassium hydroxide), 8, II
14.3. Transport hazard class(es)	
8	8

Alkalisch schuim super


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IATA
	
14.4. Packing group	
II	II
14.5. Environmental hazards	
Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available	

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: C5
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP15
Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP2, TP27
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Hazard identification number (Kemler No.)	: 80
Orange plates	: 
Tunnel restriction code (ADR)	: E
EAC code	: 2R

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 8L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Germany

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Amines, coco alkyldimethyl, N-oxides is listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.

Alkalisch schuim super

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.